



DETAS S.p.A. Divisione D-Power - via Treponti 29 – I-25086 Rezzato (BS)

Tel. +39 0302594120 Fax +39 0302792864 [E-Mail=info@d-power.com](mailto:info@d-power.com) URL=www.d-power.com

FlashLED vs D-Blitz



Features		FlashLED	D-Blitz
In compliance with EN 12352		L8G P0; C1; R0; A0(A1); I1; F3; O3; T1; S0	L8G (L8L on request) P0; C1; R0; A0(A1); I1; F3; O3; T1; S0
Light Source		LED	XENON
Expecting life of the light source		<u>10 years</u>	1 years
Optics		Single or Double Side	
Emitting Area		254 cm ²	
Position switch		2 positions switch: OFF, ON (night only) on request with also ON (day and night)	3 positions switch: OFF, ON (day and night) and ON (night only)
Blink/Minute		50 ± 3	60 ± 3
Twilight Switch		< 260 LUX	
Operating time with 2 pcs battery 7Ah 6V H4R25		<u>Single side 1000 hours</u> <u>Double side 500 hours</u>	50 hours
Works with		1 or 2 battery 6V H4R25	
Overall Dimensions (approx.)	Height	370	
	Width	180	
	Thickness	80	
Weight		1.7 Kg (with 2 batteries)	
Operating temperature		-10÷55 °C	
Lamp Clamp		On request for poles max Ø 48 mm or max Ø 82 mm	